

SPECIFICATION SHEET

ODYSSEY 1000

CONSTRUCTION	Scroll Loop Pile
FIBRE COMPOSITION	100% Solution Dyed Olefin
YARN TYPE	BCF
PILE WEIGHT	1000 g/m2
TOTAL WEIGHT	2000 g/m2 (+/-5%)
TUFT DENSITY	145780/sqm
TUFTED GAUGE	1/10 "
PRIMARY BACKING	Woven
SECONDARY BACKING	Action Back
CARPET WIDTH	3.66m or 4.00m
PILE HEIGHT	8.0mm
TOTAL HEIGHT	10.0mm
PILE TREATMENT	Walk of Fame

PERFORMACE SPECIFICATION

VOC EMISSION	ASTM D5116-06	<0.5 mg/m²/hour (CRI GLP)
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
COLOR FASTNESS	AATCC/16	4/5 on Grey Scale
SOILING PROPENSITY	ASTM D 6540-00	4







- Shading or Pile reversal is an inherent attribute of cut pile carpets and it is not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies

