

SPECIFICATION SHEET

COMMON GROUND

CONSTRUCTION	LOOP
FIBER COMPOSITION	100% Nylon (Polyamide6)
YARN TYPE	BCF
DYE METHOD	Solution Dyed
PILE WEIGHT	700g/m2
NUMBER OF TUFTS	222780/m2
TUFT GAUGE	1/12"
PRIMARY BACKING	Non-Woven
SECONDARY BACKING	StableShield 100% Vinyl
OPTIONAL BACKING	Recova-Pu Cushion, Eco Shield 100% Recycled Vinyl
TILE SIZE	50x50cm
PILE HEIGHT	3.0mm-5.0mm
TOTAL HEIGHT	7.0mm
PILE & BACKING TREATMENT	INVISTA Anti-Soil Treatment, Anti Microbial Treatment (optional)
RECOMMENDED	Quarter Turn or Monolithic

PERFORMANCE SPECIFICATION

WEAR CLASSICATION	HEAVY CONTRACT	
VOC EMISSION	ASTM D5116-06	<0.5 mg/m²/hour (CRI GLP)
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
CRITICAL RADIANT FLUX	ASTM E648-08	Class 1
STATIC PROPENSITY	ISO 6356	0.2 kV
COLOR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	ISO 8302	.04m2 K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	EN ISO 11654	aw: 0.15(H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	< 0.20%
CASTOR CHAIR TEST	DIN 54324	R ≥ 2.4
SMOKE DENSITY	EN ISO 9239-1:2002	<450









































- Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of $\pm \, 5\%$
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies