

SPECIFICATION SHEET

MODERN BOUTIQUE

CONSTRUCTION	LOOP	
PILE FIBER COMPOSITION	100% Nylon (Polyamide 6)	
YARN TYPE	Cable	
DYE METHOD	Solution Dyed	
PILE WEIGHT	610g/m2	
NUMBER OF TUFTS	194340/m2	
TUFTING GAUGE	1/12"	
PRIMARY BACKING	Non-Woven	
SECONDARY BACKING	Stable Shield - 100% Vinyl	
OPTIONAL BACKINGS	Recova-PU Cushion , EcoShield-100% Recycled Vinyl	
TILE SIZE	50 cm x 50 cm	
PILE HEIGHT	2.5 mm / 5.3 mm	
TOTAL HEIGHT	8.0 mm	
PILE TREATMENT	INVISTA Anti-Soil Treatment, Anti-Microbial (optional)	
RECOMMENDED	Quarter Turn or Brick	

PERFORMANCE SPECIFICATION

WEAR CLASSIFICATION	Heavy Contract	
VOC EMMISION	ASTM D5116-06	<0.5 mg/m²/hour
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630 Pass 8/8	
CRITICAL RADIANT FLUX	ASTM E648-08	Class 1
STATIC PROPENSITY	ISO 6356	0.2 kV
COLOUR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	ISO 8302	.04m²K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	EN ISO 11654	aw: 0.15(H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	< 0.20%
CASTOR CHAIR TEST	DIN 54324	R≥2.4
SMOKE DENSITY	EN ISO 9239-1:2002	< 450








































Color may slightly vary from one dye lot to another dye lot

Total weight of the product can have a normal variation of ± 5%

We reserve the right to amend the above specification without prior notice with changes in raw material supplies

