

# CARPET TILES SPECIFICATION SHEET

## MOMENTUM

CONSTRUCTION	Loop Pile
PILE FIBER COMPOSITION	100% Nylon (Polyamide 6)
YARN TYPE	BCF
DYE METHOD	Solution Dyed
PILE WEIGHT	700/m <sup>2</sup>
NUMBER OF TUFTS	199080/m <sup>2</sup>
TUFTING GAUGE	1/12"
PRIMARY BACKING	Non-Woven
BACKING STRUCTURES	Stable Shield 100% Vinyl
TILE SIZE	50x50cm
PILE HEIGHT	3.5mm/5.0mm
TOTAL HEIGHT	7.50mm
PILE TREATMENT	INVISTA Anti-Soil Treatment, Anti-Microbial (optional)
RECOMMENDED	Quarter Turn or Brick

## PERFORMANCE SPECIFICATION

WEAR CLASSIFICATION	HEAVY CONTRACT	
VOC EMISSION	ASTM D5116-06	<0.5 mg/m <sup>2</sup> /hour (CRI GLP)
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
CRITICAL RADIANT FLUX	ASTM E648-08	Class 1
STATIC PROPENSITY	ISO 6356	0.2 kV
COLOR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	ISO 8302	.04m <sup>2</sup> K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	EN ISO 11654	αw: 0.15(H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	< 0.20%
CASTOR CHAIR TEST	DIN 54324	R ≥ 2.4
SMOKE DENSITY	EN ISO 9239-1:2002	<450



- Shading or Pile reversal is an inherent attribute of cut pile carpets and it is not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies



Standard Carpets Ind LLC  
P.O. Box No. 490014  
Dubai Industrial Park, Dubai UAE  
T: +971 4 554 7137 | F: +971 4 554 7132  
E: info@standardcarpets.com | www.standardcarpets.com

Standard Carpets Ind LLC  
P.O. Box No. 490014  
Dubai Industrial Park, Dubai UAE  
Made In The UAE. The largest manufacturer of tufted carpets and  
the only manufacturer of carpet tiles in the United Arab Emirates.

Standard Carpets are manufactured under the  
environmental quality system certified and complying  
with ISO 18001 by an accredited certification body.