



TRICK OR TREAT

CONSTRUCTION	LOOP
PILE FIBER COMPOSITION	100% Solution Dyed Olefin
YARN TYPE	BCF
PILE WEIGHT	600 g/m ²
NO. OF TUFTS	177750 / m ²
TUFTING GAUGE	1/10"
PRIMARY BACKING	Non-Woven
SECONDARY BACKING	Stable Shield-100 % Vinyl
TILE SIZE	50 cm x 50 cm
PILE HEIGHT	3.5 mm
TOTAL HEIGHT	6.5 mm
PILE TREATMENT	INVISTA Anti-Soil Treatment
RECOMMENDED	Quarter Turn and Brick

PERFORMANCE SPECIFICATION

VOC EMISSION	ASTM D5116-97	<0.5 mg/m ² /hour
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
REACTION TO FIRE	EN ISO 9239-1	Dfl-s 1
STATIC PROPENSITY	ISO 6356	0.2 kV
COLOUR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	ISO 8302	.04m ² K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	EN ISO 11654	αw: 0.15(H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	< 0.20%
CASTOR CHAIR TEST	DIN 54324	R ≥ 2.4



10 YEAR
Wear Warranty

LIFETIME
Stain Resistance Warranty



LIFETIME
Soil Resistance Warranty

LIFETIME
Colour Fastness Warranty

Quarter Turn

Brick

- Due to Carpet Manufacturing Process, mass specification are Subject to ± 10% variation
- Shading or Pile reversal is nature of cut pile carpet and it is not manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- We reserve to amend the above specification without prior notice due variables in raw material supplies

Standard Carpets Ind LLC
Made In The UAE. The largest manufacturer of tufted carpets and the only manufacturer of carpet tiles in the United Arab Emirates.

Standard Carpets are manufactured under the environmental quality system certified and complying with ISO 18001 by an accredited certification body.

