



# CO-PILOT

|                   |                         |
|-------------------|-------------------------|
| CONSTRUCTION      | Multilevel Loop         |
| PILE COMPOSITION  | 100% Olefin             |
| YARN TYPE         | BCF                     |
| DYE METHOD        | Solution Dyed           |
| PILE WEIGHT       | 750g/m <sup>2</sup>     |
| NUMBER OF TUFTS   | 197000/m <sup>2</sup>   |
| TUFTED GAUGE      | 1/10"                   |
| PRIMARY BACKING   | Non-Woven               |
| SECONDARY BACKING | StableShield 100% Vinyl |
| TILE SIZE         | 50x50cm                 |
| PILE HEIGHT       | 4.2mm                   |
| TOTAL HEIGHT      | 7.2mm                   |
| RECOMMENDED       | Quarter Turn or Brick   |

## PERFORMANCE SPECIFICATION

|                         |                                  |  |
|-------------------------|----------------------------------|--|
| VOC EMISSION            | ASTM D5116-17                    | <0.5 mg/m <sup>2</sup> /hour (CRI GLP) |
| FLAMMABILITY            | ASTM D-2859//FF 1-70//16CFR 1630 | Pass 8/8                               |
| STATIC PROPENSITY       | AATCC 134-2011                   | 0.2 kV                                 |
| COLOR FASTNESS          | AATCC/16                         | 5/5 on Grey Scale                      |
| THERMAL RESISTANCE      | DIN 52612                        | .04m <sup>2</sup> K/W                  |
| IMPACT SOUND INSULATION | ISO 140-8                        | ΔLw 23dB                               |
| SOUND ABSORPTION LEVEL  | DIN EN ISO 11654                 | αw: 0.15(H)                            |
| DIMENSIONAL STABILITY   | ISO 3018                         | < 0.20%                                |



- Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies

