

SPECIFICATION SHEET

EASY LINE

CONSTRUCTION	SCROLL LOOP PILE
PILE FIBER COMPOSITION	100% Olefin
YARN TYPE	BCF
DYE METHOD	Solution Dyed
PILE WEIGHT	650g/m ²
NUMBER OF TUFTS	236400/m ²
TUFTING GAUGE	1/10"
PRIMARY BACKING	Non-Woven
BACKING STRUCTURES	Stable Shield 100% Vinyl
TILE SIZE	25 x 100 cm
PILE HEIGHT	4.0 mm(+/-0.5mm)
TOTAL HEIGHT	7.0 mm(+/-0.5mm)
RECOMMENDED	Quarter Turn, Herringbone, Ashlar or Brick

PERFORMANCE SPECIFICATION

VOC EMISSION	ASTM D5116-17	<0.5 mg/m ² /hour (CRI GLP)
FLAMMABILITY	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
STATIC PROPENSITY	AATCC 134-2011	0.2 kV
COLOR FASTNESS	AATCC/16	5/5 on Grey Scale
THERMAL RESISTANCE	DIN 52612	.04m ² K/W
IMPACT SOUND INSULATION	ISO 140-8	ΔLw 23dB
SOUND ABSORPTION LEVEL	DIN EN ISO 11654	αw: 0.15(H)
DIMENSIONAL STABILITY	ISO 3018	< 0.20%



Standard
CARPETS

- Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies