CARPET TILES 5 PECIFICATION SHEET

UTOPIA

| LOOP |
|--|
| 100% Olefin |
| BCF |
| Solution Dyed |
| 650g/m2 |
| 4600g/m2 (+/-5%) |
| 184860/m2 |
| 1/12" |
| Non-Woven |
| StableShield 100% Vinyl |
| 50x50cm |
| 2.3mm / 5.5mm |
| 8.0mm |
| INVISTA Anti-Soil Treatment, Anti Microbial (optional) |
| Quarter Turn or Brick |
| |

PERFORMANCE SPECIFICATION

| VOC EMISSION | ASTM D5116-06 | <0.5 mg/m²/hour (CRI GLP) |
|-------------------------|----------------------------------|---------------------------|
| FLAMMABILITY | ASTM D-2859//FF 1-70//16CFR 1630 | Pass 8/8 |
| REACTION TO FIRE | EN ISO 9239-1:2002 | Dfl-s1 |
| STATIC PROPENSITY | ISO 6356 | 0.2 kV |
| COLOR FASTNESS | AATCC/16 | 5/5 on Grey Scale |
| THERMAL RESISTANCE | ISO 8302 | .04m2 K/W |
| IMPACT SOUND INSULATION | ISO 140-8 | ΔLw 23dB |
| SOUND ABSORPTION LEVEL | EN ISO 11654 | aw: 0.15(H) |
| SOILING PROPENSITY | ASTM D 6540-00 | 4 |
| DIMENSIONAL STABILITY | EN 986 | < 0.20% |
| CASTOR CHAIR TEST | DIN 54324 | R ≥ 2.4 |













Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect

- Color may slightly vary from one dye lot to another dye lot
 Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies

Standard Carpets Ind LLC P.O. Box No. 490014 Dubai Industrial Park, Dubai UAE T: +971 4 554 7137 | F: +971 4 554 7132 E: info@standardcarpets.com | www.standardcarpets.com Standard Carpets Ind LLC P.O. Box No. 490014 Dubai Industrial Park, Dubai UAE Made In The UAE. The largest manufacturer of tufted carpets and the only manufacturer of carpet tiles in the United Arab Emirates. Standard Carpets are manufactured under the environmental quality system certified and complying with ISO 18001 by an accredited certification body.