

LAST CHANCE






CONSTRUCTION	LOOP
PILE FIBER COMPOSITION	100% Olefin
YARN TYPE	BCF
DYE METHOD	Solution Dyed
PILE WEIGHT	650g/m ²
NUMBER OF TUFTS	184860/m ²
TUFTING GAUGE	1/12"
PRIMARY BACKING	Non-Woven
SECONDARY BACKING	Stable Shield - 100% Vinyl
OPTIONAL BACKING	Recova-PU Cushion , EcoShield-100% Recycled Vinyl
TILE SIZE	50 cm x 50 cm (19.6 in x 19.6 in)
PILE HEIGHT	2.3 mm / 5.5 mm
TOTAL HEIGHT	8.00 mm
PILE TREATMENT	INVISTA Anti-Soil Treatment, Anti-Microbial (optional)
RECOMMENDED INSTALLATION	Quarter Turn or Brick

SPECIFICATIONS


COLOURLINE




LAST CHANCE - 647



LAST CHANCE - 648




LAST CHANCE - 649



LAST CHANCE - 652




LAST CHANCE - 655




LAST CHANCE - 657




LAST CHANCE - 677



LAST CHANCE - 678



LAST CHANCE - 679




LAST CHANCE - 685




HOW TO INSTALL

QUARTER TURN



BRICK





Standard
CARPETS

www.standardcarpets.com