

QUICK & EASY FLOOR INSTALLATION GUIDE



QUICK & EASY FLOOR INSTALLATION GUIDE

PLEASE REMOVE TILES FROM BOXES
FOR 24 HOURS PRIOR TO INSTALLATION.

Tools

- I. Carpet Knife, Tape Measure, Chalk, Straight Edge
- II. Adhesive or Double-sided tape

Step 1:

Measure the size of the room – (length*width) to determine the size of the room. If the room is not a perfect square, then divide the room into smaller rectangles to obtain total area of the room. Each box has 20 tiles equivalent to 5 square meters. Remove old carpet and clear the working area of all furniture. The floor must be dry, clean, level and free from debris. Cracks and holes must be filled for maximum performance.




QUICK & EASY FLOOR INSTALLATION GUIDE


Step 2:

Divide the room into 4 equal parts using the chalk and straight edge. Apply the adhesive or the gridlines using double sided tape. Since this is a graphic carpet design, the tiles should be laid quarter-turned or at 90 degrees as shown below. Directional arrows are printed at the back of the tiles. You can start from either the centre of the room or from the corner and shown in 1 and 2 below.


I. Starting in corner of room



II. Starting in centre of room



Quarter turn/Parquet



Turn tiles 90 degrees, every other tile



QUICK & EASY FLOOR INSTALLATION GUIDE

Step 3:

Tiles overlapping with the side walls can be cut using a carpet knife. Using a straight edge and chalk as a guide, slowly cut the borders. It is advisable to cut the tile from the back to get a clean finish. For a clean finish, place a new tile backwards on top of the overlapping tile and draw a reference line to cut the tile.

Precautions:

When moving heavy furniture, use runners to avoid shifting. Maximum working temperature is 50 degree Celsius.

Replacement and Maintenance:

Heavily damaged tiles can be replaced from old stock or buying new from the store. Any visual remarks from the new tile will disappear over a short time. Use vacuum cleaners to prevent the effect of soiling. In case of stains, use the regular stain removers.





Standard
CARPETS